YJH 系列变频中压无油螺杆空压机

YJH SERIES VFD MEDIUM-PRESSURE OIL-FREE SCREW AIR COMPRESSOR

YJH 系列水润滑无油单螺杆变频中压空压机它是由双机头、双电机、双变频二级压缩实现，压力可达到 30 公斤、40 公斤，是 PET 吹瓶工艺较佳的配套设备。本公司也接受 15 公斤以上非标不同规格的订制。广泛应用于燃气、沼气、二氧化碳、煤层气、瓦斯、氮气、氧气等特殊气体的压缩机。

YJH Series Water-Lubricated Oil-Free Single-Screw VFD Medium-Pressure Air Compressor adopts two-stage compression with dual heads, dual motors and dual variable frequency drives. It can reach pressures of 30 bar and 40 bar, making it an ideal supporting equipment for PET blow molding processes. Our company also accepts custom non-standard specifications above 15 bar.Special gas compressors widely used for gas, biogas, carbon dioxide, coalbed methane, mine gas, nitrogen and oxygen.

YJH Series



2.0~4.0MPa 中高压
Medium & High Pressure 2.0~4.0MPa

双机头双变频
Dual-head Dual VFD

PET 吹瓶专用
For PET Blow Molding

型号	功率	压力	排气量	外形尺寸 L×W×H	重量	噪音	出口管径
	KW	Mpa	m^3/min	mm	kg	(dB)A	inch
YJH55A/W	37+15	2.0	6	3100*1600*1900(A)	1850(A)	70	1-1/4″
				3100*1600*1600(W)	1400(W)	70	
YJH60A/W	37+22	3.0	6	3100*1600*1900(A)	2000(A)	70	1″
				3100*1600*1600(W)	2000(W)	70	
YJH75A/W	45+30	4.0	6	3100*1600*1900(A)	2100(A)	70	1″
				3100*1600*1600(W)	2100(W)	70	
YJH82A/W	45+37	2.0	10	3800*1800*2200(A)	3000(A)	73	1-1/4″
				3400*1800*1700(W)	2300(W)	73	
YJH90A/W	55+37	3.0	10	3800*1800*2200(A)	3000(A)	73	1-1/4″
				3400*1800*1700(W)	2300(W)	73	
YJH120A/W	55+55	4.0	10	3800*1800*2200(A)	3400(A)	73	1-1/4″
				3400*1800*1700(W)	2400(W)	73	
YJH112A/W	75+37	2.0	13	3800*1800*2200(A)	3500(A)	73	1-1/2″
				3400*1800*1700(W)	2700(W)	75	
YJH120A/W	75+45	3.0	13	3800*1800*2200(A)	3500(A)	75	1-1/4″
				3400*1800*1700(W)	2900(W)	75	
YJH150A/W	75+75	4.0	13	3800*1800*2200(A)	3000	75	1-1/2″
				3400*1800*1700(W)		75	
YJH130W	75+55	2.0	16	3800*1900*1900	3500	77	1-1/2″
YJH150W	90+65	3.0	16	3800*1900*1900	3500	77	1-1/2″
YJH185W	110+75	4.0	16	3800*1900*1900	3500	77	1-1/2″
YJH165W	110+55	2.0	20	3800*1900*1900	4000	78	2″
YJH185W	110+75	3.0	20	3800*1900*1900	4000	78	2″
YJH220W	110+110	4.0	20	3800*1900*1900	4000	78	2″
YJH200W	110+90	2.0	24	3800*1900*1900	4500	78	2″
YJH220W	132+90	3.0	24	3800*1900*1900	4500	78	2″
YJH250W	132+110	4.0	24	3800*1900*1900	4600	78	2″
YJH235W	160+75	2.0	28	4000*2000*2000	4600	78	2-1/2″
YJH270W	160+110	3.0	28	4000*2000*2000	4700	78	2″
YJH292W	160+132	4.0	28	4000*2000*2000	4800	78	2″
YJH292W	160+132	2.0	36	4300*2100*2100	5000	80	2-1/2″
YJH332W	200+132	3.0	36	4300*2100*2100	5000	80	2-1/2″
YJH385W	200+185	4.0	36	4300*2100*2100	5000	80	2-1/2″
YJH317W	185+132	2.0	40	4300*2100*2100	5000	80	2-1/2″
YJH380W	220+160	3.0	40	4300*2100*2100	5000	80	2-1/2″
YJH410W	250+160	4.0	40	4300*2100*2100	5000	80	2-1/2″